

TECH LINE Coatings

SAFETY DATA SHEET

Section 1 – Identification

Product Identifier: Polyphen Hot Stop Thermal Barrier

Part Number: TLHB

Recommended Use: Thin film Thermal Barrier Coating

Restrictions on Use:

Manufacturer / Supplier:

Tech Line Coatings, Inc
26844 ADAMS AVE.
MURRIETA, CA 92562
USA
Phone 951-304-0834
Fax 951-461-9658
www.techlinecoatings.com

**Keep out of reach of children.
For Industrial Use Only
Not recommended for use on Medical equipment.
Not recommended for use on Aviation equipment.**

Emergency Phone: (Chemtrec) 1-800-424-9300

Section 2 – Hazards Identification

Signal Word: Danger

Symbols:



Hazard Statements:

Highly Flammable Liquid and Vapor
Toxic if Swallowed
Toxic in Contact With Skin
Toxic if Inhaled
Causes Skin Irritation
Causes Serious Eye Irritation
Suspected of causing cancer
Suspected of genetic defects
Suspected of damaging fertility or the unborn child
Causes damage to organs (Eyes, Kidney, Liver, Central Nervous System, Heart)
May cause damage to organs (Pancreas, Spleen)
May cause damage to organs (Kidney, Liver, Central Nervous System, Pancreas, Spleen) through prolonged or repeated exposure.

GHS Classification:

Category

Flammable Liquid	2
Acute Toxicity Oral	3
Acute Toxicity Dermal	3
Acute Toxicity Inhalation	3
Skin Irritation	2
Eye Irritation	2A
Carcinogenicity	2
Germ Cell Mutagenicity	2
Reproductive Toxicity	2
Specific Target Organ Toxicity Single Exposure	1
Specific Target Organ Toxicity Single Exposure	2
Specific Target Organ Toxicity Repeated or Prolonged Exposure	2

Precautionary Statements:

Keep away from heat / sparks / open flames / hot surfaces. - No Smoking. Ground / bond container and receiving equipment. Use explosion proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

In case of fire use alcohol-resistant foam, dry chemical or carbon dioxide

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Wear protective gloves / protective clothing (chemical proof). Wear eye protection and face protection. Wash hands, face and any exposed skin thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat drink or smoke when using this product. Do not breath fumes / mist / vapors / spray. Use only outdoors or in a well ventilated area.

If swallowed: immediately call a poison center / doctor for medical advice. Rinse mouth with water.

If on skin: wash with plenty of water. Call a poison center / doctor if you feel unwell or if irritation occurs. Immediately take off all contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center / doctor for medical advice.

If in eyes: Rinse cautiously in water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advise / attention.

If exposed or concerned: Get medical advise / attention, from a poison center / doctor.

Dispose of Contents / container in accordance with regulations in your area. See section 13 for additional information.

Section 3 – Composition / Information On Ingredients

Component Name	Common Name / Synonyms	CAS#	% of Weight
Methyl Ethyl Ketone	MEK	78-93-3	15 - 20%
Ethanol	Ethyl Alcohol	64-17-5	30 - 40%
Phenol	Hydroxybenzene	108-95-2	4 - 5%
Molybdenum Disulfide	MoS ₂	1317-33-5	Trade Secret
Methanol	Methyl Alcohol	67-56-1	2 - 4%
Dimethyl Phthalate		131-11-3	2 - 2.50%
Formaldehyde		50-00-0	0.1 - 0.3%

Section 4 – First Aid Measures

General advise:

- Consult a physician. Show this Safety Data Sheet to the doctor in attendance. Move out of dangerous area.

After EYE Contact:

- Immediately irrigate with plenty of water for 15 minutes. Obtain medical attention if irritation persists.

After SKIN Contact:

- Remove contaminated clothing without delay. Flush skin thoroughly with water. Do not reuse clothing without laundering.

After INHALATION:

- Administer oxygen if there is difficulty in breathing. Obtain medical attention immediately if necessary.

After SWALLOWING:

- Call a physician immediately, ONLY induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person.

See section 11 for additional information

Notes to Physician: Treat symptomatically.

Section 5 – Fire Fighting Measures

Extinguishing Media:

- Water spray, alcohol resistant foam, co2, dry chemical, dry sand. Cool closed containers exposed to fire with water spray.

Special Fire Fighting Procedures:

- Use full protective equipment, including self contained breathing apparatus

Unusual Fire And Explosion Hazards:

- During emergency conditions, overexposure to decomposition products may cause a health hazard. Hazardous

polymerization may take place if exposed to fire conditions. Water runoff can cause environmental damage, dike and collect water used to fight fire.

Specific Hazards Arising from the Chemical:

- Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.
- Containers may explode when heated.

Section 6 – Accidental Release Measures

Methods for Containment and Clean Up

- Turn off all sources of heat or ignition.
- Soak up with inert absorbent material.
- Keep in suitable, marked and closed containers for disposal.
- Use spark-proof tools and explosion-proof equipment.
- Remove sources of ignition.
- Warn other workers of spill.
- Wear protective equipment
 - NIOSH Approved Respirator
 - Gloves
 - Safety Glasses
- Stop leak if you can do so without risk.
- Do not allow material to be released into the environment.
- Retain all contaminated water for removal and treatment. DO NOT flush to sewer.

Additional Information:

- See Section 7 for safe handling information.
- See Section 8 for PPE information
- See Section 13 for disposal information

Section 7 – Handling And Storage

Handling:

Do not breathe vapors or mists from spraying. Avoid contact with skin and eyes. Use with adequate ventilation to maintain exposure levels below established exposure limits. Wear personal protective equipment. If required wear an appropriate NIOSH approved respirator with paint prefilter. Use explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage:

Store in area suitable for flammable liquids. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Protect from oxidizers, inorganic acids, aldehydes, and isocyanates.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Component	ACGIH TLV	OSHA PEL	
Methyl Ethyl Ketone	200 PPM	200 PPM	
Ethanol	1000 PPM	1000 PPM	
Molybdenum Disulfide	10 mg/m3	10 mg/m3	
Methanol	200 PPM	200 PPM	
Dimethyl Phthalate	5 mg/m3	5 mg/m3	
Phenol	5 PPM (SKIN)	5 PPM (SKIN)	
Formaldehyde	CEIL 0.3 ppm	TWA 0.75 ppm STEL 2 ppm	

Engineering Controls: Exhaust ventilation.
Showers

Respiratory Protection: Eyewash stations
 Use in a well-ventilated area.
 Use NIOSH approved respirator if TWA/TLV limits are exceeded
Protective Gloves: CHEMICAL RESISTANT
Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES
Other Protective Equipment: WEAR PROTECTIVE CLOTHING, CHEMICAL RESISTANT OR OTHER PROTECTIVE
 OUTERWEAR, AVOID CONTACT WITH SKIN OR EYES
Ventilation: Local Exhaust: Use To Maintain Below TWA Limits
Mechanical: Use Non-Sparking Equipment
Work / Hygienic Practices: wash thoroughly after handling product and before eating, drinking or smoking

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Form :	liquid
Color :	Black
Odor :	Strong Alcohol/Solvent Smell
Odor Threshold:	Not Established
pH :	Not Established
Melting point / Freezing point:	Not Established
Initial boiling point :	131 – 280° F
Flash point :	> 16° F
Evaporation Rate:	Not Established
Upper/lower flammability or explosive limits:	Not Established
Vapor pressure	Not Established
Vapor density	Not Established
Relative density	Not Established
Solubility(ies)	Water: poor
Partition coefficient: n-octanol/water	Not Established
Auto-ignition temperature	Not Established
Decomposition temperature	Not Established
Viscosity	Not Established
Total VOC	5.42 lbs/gal

SECTION 10 – STABILITY AND REACTIVITY

Stability: STABLE
Possibility of hazardous reactions: Hazardous Polymerization: Will not occur.
Conditions to avoid: Avoid storage of open containers at elevated temperatures.
Incompatible Materials: oxidizers, inorganic acids, aldehydes, and isocyanates
Hazardous Decomposition Products: Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silicon dioxide. Carbon oxides. Formaldehyde.

SECTION 11 – TOXICOLOGICAL INFORMATION

Potential Health Effects

Inhalation

Toxic if inhaled. Causes respiratory tract irritation.

Ingestion

Toxic if swallowed.

Skin

Toxic if absorbed through skin. Causes skin irritation.

Eyes

Causes eye irritation.

Acute Toxicity

Methyl Ethyl Ketone	Oral LD50	LD50 Oral - rat - 2,737 mg/kg
	Inhalation LC50	LC50 Inhalation - mouse - 4 h - 32,000 mg/m ³ LC50 Inhalation - Mammal - 38,000 mg/m ³
	Dermal LD50	LD50 Dermal - rabbit - 6,480 mg/kg
Ethanol	Oral LD50	LD50 Oral - rat - 7,060 mg/kg Remarks: Lungs, Thorax, or Respiration:Other changes.
	Inhalation LC50	LC50 Inhalation - rat - 10 h - 20000 ppm
	Dermal LD50	no data available
Phenol	Oral LD50	LC50 Inhalation - Rat - 4-hr 4,470 ppm (33.0 mg/l) LD50 Oral - rat - 317.0 mg/kg Remarks: Behavioral:Convulsions or effect on seizure threshold. LD50 Oral - rat - 410.0 - 650.0 mg/kg
	Inhalation LC50	LC50 Inhalation - rat - 8 h - 900 mg/m ³
	Dermal LD50	LD50 Dermal - rabbit - 630.0 mg/kg
Molybdenum Disulfide	Oral LD50	no data available
	Inhalation LC50	LC50 Inhalation - rat - 4 h - > 2,820 mg/m ³ Remarks: Lungs, Thorax, or Respiration:Other changes.
	Dermal LD50	no data available
Methanol	Oral LD50	LDLO Oral - Human - 143 mg/kg Remarks: Lungs, Thorax, or Respiration:Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. LD50 Oral - rat - 1,187 - 2,769 mg/kg
	Inhalation LC50	LC50 Inhalation - rat - 4 h - 128.2 mg/l LC50 Inhalation - rat - 6 h - 87.6 mg/l
	Dermal LD50	LD50 Dermal - rabbit - 17,100 mg/kg
Dimethyl Phthalate	Oral LD50	LD50 Oral - rat - 8,239 mg/kg
	Inhalation LC50	no data available
	Dermal LD50	LD50 Dermal - rabbit - > 11,940 mg/kg
Formaldehyde	Oral LD50	No data available
	Inhalation LC50	No data available
	Dermal LD50	No data available

Skin Corrosion/Irritation

In skin irritation studies, the compound was found to be slightly to moderately irritating.

Serious Eye Damage/Eye Irritation

In eye irritation studies, the compound was found to be slightly to moderately irritating.

Respiratory Or Skin Sensitization

No data available

Germ Cell Mutagenicity

Phenol

In vitro tests showed mutagenic effects

Methanol

Genotoxicity in vitro - Ames test - *S. typhimurium* - with and without metabolic activation – negative

Genotoxicity in vitro - in vitro assay - fibroblast - negative

Mutation in mammalian somatic cells.

Genotoxicity in vivo - mouse - male and female - Intraperitoneal – negative

Carcinogenicity

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Phenol)
1 – Group 1: Carcinogenic to humans (Formaldehyde)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Reasonably anticipated to be a human carcinogen (Formaldehyde)
Known to be human carcinogen (Formaldehyde)

OSHA: May Cause Cancer (formaldehyde)

This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive Toxicity

Dimethyl Phthalate

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific Target Organ Toxicity Single Exposure

Methanol

Causes damage to organs

Specific Target Organ Toxicity Repeated Or Prolonged Exposure

Phenol

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

No data available

SECTION 12 – ECOLOGICAL INFORMATION

General Comments: Do not allow material to be released into the environment without proper governmental permits

Environmental Toxicity:

Methyl Ethyl Ketone

Toxicity to fish

mortality NOEC - *Cyprinodon variegatus* (sheepshead minnow) - 400 mg/l - 96 h
LC50 - *Pimephales promelas* (fathead minnow) - 3,130 - 3,320 mg/l - 96 h

Toxicity to daphnia and other aquatic

LC50 - *Daphnia magna* (Water flea) - > 520 mg/l - 48 h

invertebrates	EC50 - Daphnia magna (Water flea) - 7,060 mg/l - 24 h
Methanol	
Toxicity to fish	mortality LC50 - Lepomis macrochirus (Bluegill) - 15,400.0 mg/l - 96 h NOEC - Oryzias latipes - 7,900 mg/l - 200 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - > 10,000.00 mg/l - 48 h
Toxicity to algae	Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 22,000.0 mg/l - 96 h
Phenol	
Toxicity to fish	LC50 - Leuciscus idus (Golden orfe) - 14.00 - 25.00 mg/l - 48 h LC50 - Carassius auratus (goldfish) - 36.10 - 68.80 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 12.00 mg/l - 24 h EC100 - Daphnia magna (Water flea) - 100.00 mg/l - 24 h
Toxicity to algae	EC50 - Chlorella vulgaris (Fresh water algae) - 370.00 mg/l - 96 h

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Product :

Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated Packaging

Dispose of as unused product.

SECTION 14 – TRANSPORTATION INFORMATION

Hazardous for Shipping: Yes

Based on 49 CFR, IATA and IMDG:

UN Number: UN1263

UN Proper Shipping Name: Paint

Hazard Class: 3

Packing Group: II

Labels: Flammable Liquid

Placards: Flammable Liquid

SECTION 15 – Regulatory Information

TSCA (Toxic Substances Control Act) Regulations, 40 CFR 710: All hazardous ingredients are on the TSCA Chemical

Substance Inventory.

Component	SARA 302	SARA 311 / 312	SARA 313	Massachusetts RTK	Pennsylvania RTK	New Jersey RTK	California Prop 65 list
Methyl Ethyl Ketone	No	Yes	No	Yes	Yes	Yes	No
Ethanol	No	Yes	No	Yes	Yes	Yes	No
Phenol	Yes	Yes	Yes	Yes	Yes	Yes	No
Molybdenum Disulfide	No	No	No	Yes	Yes	Yes	No
Methanol	No	Yes	Yes	Yes	Yes	Yes	No
Formaldehyde	Yes	Yes	Yes	Yes	Yes	Yes	Yes

SARA 311 / 312 Hazards: Flammable Hazard ,Acute Health Hazard, Chronic Health Hazard

SECTION 16 – OTHER INFORMATION

Date Prepared: 06/27/2013

Date Updated:

Date Printed: 06/27/2013

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF TECH LINE COATINGS, INC., KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY TECH LINE COATINGS, INC. TO BE ACCURATE, AND TECH LINE COATINGS, INC., DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME. BEFORE USING ANY CHEMICAL, READ ITS LABEL, INSTRUCTIONS AND MATERIAL SAFETY DATA SHEET.